




Custom Engineered Agitation Solutions

The MixPro™ line of top entry gear drive agitators provides customers with a robust, reliable agitation source for high production industrial environments. The durable non-proprietary right angle reducer utilizes helical / spiral bevel gearing and was designed specifically for abusive applications. Our popular 'GTB' design utilizes process matched wet ends for optimum agitation solutions. The ruggedness of the unit has proven itself in abusive applications, consequently minimizing downtime.

This established MixPro™ design is widely recognized by industry as a leader in top entry agitation equipment.



Built to handle the toughest environments MixPro™ agitators have proven themselves time and again in high production manufacturing environments where quality and performance are paramount. Our quality assurance process tests every mixer to withstand the harshest conditions and perform to specification.



www.mixproagitators.com

SERIES OF TOP ENTRY AGITATORS

GTB

Features & Benefits

- The agitator drive is comprised of a robust non-proprietary right angle reducer which utilizes helical / spiral bevel gear sets. The minimum mechanical service factor of the gear strength as calculated on continuous operation is 1.5 (based on current AGMA and ISO standards). The thermal rating of the reducer meets or exceeds the installed motor name plate power.
- The output shaft features a “no-leak” drywell design that physically separates the oil sump from the output shaft to eliminate gear oil contamination of the tank product.
- Larger bearing span design allows for stronger shaft support for a more robust agitator installation.
- Profile controlled gas carburizing and optimal gear geometry allow for lower noise and vibration as well as maximizing load capacity.
- Unique internal design ensures oil supply to all bearings upon first oil fill.
- Maintenance free Oil-Lock™ high speed shaft seal ensures “oil-tight-for-life” design.
- Maintenance friendly reducer design aids in quick inspection and troubleshooting.
- The large diameter, high capacity output shafts are designed to accommodate the high bending moment loads associated with mixer applications.
- The agitator drive head is available in a variety of configurations, matched to the application (ie. flange mount, plate mount, with tank seal, without tank seal, etc.).
- Optional tank seal is intricate to the reducer housing, eliminating shaft misalignment.
- OSHA guarding is standard for increased safety.

Applications



Pulp & Paper

- Stock Prep Systems
- Recovery Systems
- Coating Systems
- Effluent Treatment



Mineral

- Precious Metals (gold & silver)
- Base Metals
- Effluent Treatment
- Cyanide Destruct



Non-Metallic Minerals

- Clay
- Calcium Carbonate
- Titanium Dioxide



Chemical

- Paints & Pigments
- Edible Oil
- Starch
- Petro-Chemical
- Alcohol Production
- Building Products



Wastewater/ Water Treatment

- Flocculation
- Chemical Blending
- Flash Mixers

Contact Us

Professional Mixing Equipment Inc.

22 Melanie Drive, Brampton, ON, Canada L6T 4K9

Tel: (905) 790-5444 Fax: (905) 790-5420

www.mixproagitators.com

Your local representative is:

